

## MS6000

### CARD MAILING SYSTEMS LINE



### THE EXCEPTIONAL VALUE OF DIRECT MAILING

The MS6000 Card Mailing System is a simple and affordable solution for direct card mailing and fulfilment applications. Designed to work either as a stand-alone unit or configured in-line with the S6000 card issuance line, is dedicated for a low volume issuance.

#### TARGET MARKETS

- Financial
- Government
- Retail
- Insurance
- Telecommunications

# CARD MAILING SYSTEMS

## MS6000

### CARD MAILING SYSTEMS LINE

#### CARRIER-BARCODE VERIFICATION MODULE

Ensures that cards and carriers match before combining these to the folding and insertion module.

#### BUFFERING SYSTEM

Creates a linear flow of both cards and carriers at high speed and productivity without any "parking areas" that can cause carriers and cards to become out of sequence.

#### MANAGEMENT OF MULTI CARDS

It is possible to attach up to 6 cards per carrier (up to 4 if the carrier needs to be folded). The position of each individual card on the carrier is totally configurable.

#### CARD ATTACH SENSOR

Make sure your card is well attached to the carrier with our Card Attach Sensor option, avoiding the consequences of a card's peel off during the mailing process.

#### MATICARDPRO SOFTWARE

A unique software designed to manage the entire card personalization and mailing process. It is meant also to create links and communication to the S7000 Card Personalization System. Additionally the brand new MaticardPro software provides an Advanced Exception Handling Management System. When an error occurs, in order to recover the sequence without interrupting the production process, the software guides the operator to perform the best solution, on whether to reject the card or the carrier, or both.

#### CARD REJECT TRAY & CARRIER REJECT BOX

Non-readable cards are placed in a reject tray without interrupting the production process. In case of barcode mismatch, the carrier does not need to be removed by the operator, but is automatically placed in the reject box, and normal production is continued.

#### IN-LINE CONNECTION

Adaptive link from S6000 Card Issuance System to MS6000 Card Mailing System.

## DS100

### ADAPTABLE MAIL INSERTER

#### THE EXCEPTIONAL VALUE OF DIRECT MAILING

Matica DS100 System offers total flexibility in today's mail processing market. It can be configured to almost any application, running speeds of up to 3,000 filled envelopes per hour. It is capable of processing documents from 6 different hoppers with a total pack thickness of up to 6 mm. The DS100 is a highly durable system designed and built for performance, reliability and exceptional value.

#### CONTROL PANEL

DS100 has a large, simple-to-use graphical display and control panel, which guides you through every step of the operation. By remembering your most common document types, the Select & Go function will enable you to program new jobs in seconds. Up to 20 applications can be saved and recalled by name.



#### DOCUMENT SECURITY

The hopper on DS100 is equipped with an infra-red electronic double document detection system. This accurately measures both the thickness and length of each document, ensuring the integrity of your mailings.


#### CARD FOLDER

Once the cards and carriers have been securely matched, they are passed to the DS100 to be folded and inserted. The unique folding system allows the carrier to be folded in Z, C or V formats depending on the type of envelopes to be used. Utilizing other folders and feeders from the DS100 range, up to 6 further inserts may be added to the carrier before insertion.


Z Fold



C Fold



V Fold



#### INSERT FEEDER FOR 1/3 OF A4 SHEET

Our high capacity insert feeder holds up to 300 mail pieces and features a unique separator that can easily cope with a wide variety of inserts from a single 60 gsm document up to a 4mm thick booklet. The hopper may be loaded during running in order to maximize efficiency.



## TOWER FEEDER

The tower feeder allows two different inserts to be loaded without requiring more valuable space. Each hopper has a capacity of over 200 documents.



## A4 FEEDER & FOLDER

Our powerful and versatile A4 feeder & folder is capable of producing all fold types for documents with virtually any address position. All folds are set automatically when a job is programmed. It is available with 1 hopper providing cascade capability and a maximum capacity of 500 sheets. It also enables the DS100 to work in off-line modality (not linked to MS7000 card mailing system) to allow the production of bank statements.



## EASY ACCESS

A key feature of DS100 is that your documents are easily accessible, wherever they are in the system.



## ENVELOPE FEEDER

With a hopper holding over 400 envelopes, which can be reloaded without stopping the system, DS100 handles sizes such as DL and C5 with ease. All internal guides and controls are adjusted automatically, each time an application is selected.




## OUTPUT CONVEYOR

When processing larger volumes, an output conveyor is available to stack filled envelopes in their correct order.




## CONFIGURATION OPTIONS


Configuration examples are not exhaustive - secondary modules are freely configurable.




Module	Function
1	Insert Head
2	Card Folder



Module	Function
1	Insert Head
2	Feeder
3	Card Folder



Module	Function
1	Insert Head
2	Feeder
3	Tower Feeder
4	Card Folder



Module	Function
1	Insert Head
2	A4 Feeder
3	Feeder
4	Tower Feeder
5	Card Folder

## ENVELOPE SPECIFICATIONS

Envelope Weight:

min. 70 gsm (18 lbs bond)

max. 100 gsm (26 lbs bond)

Hopper Capacity: 350 - 400 of 80 gsm (20 lbs bond) envelopes

General Requirements:

- windows must be securely gummed
- side seams must be glued to the top
- pre-scored flap crease to enable the envelope to open flat no twisting, curling or distortion evident
- matt and semi-gloss finishes are acceptable. Gloss finishes require approval from Technical Support Dept
- envelopes not meeting the above requirements may be acceptable, subject to testing and approval by Technical Support Dept
- envelopes not meeting the above requirements may affect the machine performance



## TECHNICAL SPECIFICATIONS MS6000

### Productivity

- Speed: up to 1000 cph
- Recommended operating time: 16 hours/day

### Card & Consumables Handling

- Input hopper capacity: 250 cards
- Reject hopper for non readable cards
- Cards format: ISO Std. CR80 - 0.76 mm
- Number of cards per carrier: 6 (4 if to be folded)
- Labels roller quantity: 6000

### Carrier Paper Handling

- Carrier formats: A4 or US letter size
- Recommended paper thickness: 100 gsm<sup>2</sup>
- Reject carrier box
- Carrier cooling system
- Carrier buffering system: 2 carriers
- Carrier-Data-Barcode Verification Module (carrier/card matching)
- Carrier-Stock-Barcode Verification Module (carrier/layout matching)

### Card Data Capture & Matching

- Magnetic Stripe Encoding Station
- Card Attached Sensor x2

### Other Features

- Optional in-line with the adaptive link to S6000 line
- Monitor and keyboard support

### Communication Interface

- USB

### Software

- MaticardPro for Windows® 7
- Diagnostic and setup software included

### Dimensions

- L x W x H: 110 x 120 x 125 cm

### Electrical Requirements

- Power supply: 100 to 240 VAC; 50/60Hz

\* Indicated speed is measured using Kyocera 9530 printer.

## TECHNICAL SPECIFICATIONS DS100

### Technical Features

- 1-3 feed modules (up to 6 hoppers)
- Handles stationery from 80 gsm to 4 mm thick booklets
- Inserts collated packs up to 6 mm thick
- Fully automatic fold and envelope settings
- 20 user programmable job memories
- Cycles at up to 3000 filled envelopes per hour
- Advanced operator interface
- Advanced double document calibration

### Inserting Head

- Envelope size:
  - depth: 89 mm - 165 mm
  - width: 152 mm - 264 mm
- Insert pack thickness: 6 mm
- Cycle speed: up to 4500 per hour

### Card Folder Specifications

- Fold types: Z fold, C fold & V fold capable
- Carrier size: up to 216 mm wide by up to 406 mm long
- Cards/Carrier: up to 4 cards, middle and lower panel only
- Attachment: cards must be stuck securely on to carrier
- Paper weight: min. 80 gsm - max. 100 gsm
- Speed: up to 3000 per hour

### Insert Feeder

- Material size:
  - depth: 76 mm - 152 mm
  - width: 140 mm - 242 mm
- Minimum weight: 60 gsm single sheet
- Maximum thickness: 4 mm

### Folder

- Material size:
  - depth: 140 mm - 406 mm
  - width: 140 mm - 228 mm
- Weight: 60 gsm - 120 gsm single sheet
- Up to 8 sheets, 80 gsm

### Conveyors' Dimensions

- L x W x H: 110 x 26 x 82 cm
- L x W x H: 185 x 26 x 82 cm

### Total Dimensions

- L x W x H: 278 x 69 x 53 cm

**Matica**  
SYSTEM

Matica System S.p.a.

Via Guido Rossa 4/6

20037 Paderno Dugnano, Italy

Phone: + 39 02 922 72501

Email: info@maticasystem.com

Discover our high security identification solutions at [www.edisecure.com](http://www.edisecure.com)

[WWW.ICSCORP.CO](http://WWW.ICSCORP.CO)

[www.maticasystem.com](http://www.maticasystem.com)

Data subject to change without notice. All trademarks stated are the property of their respective owners. MS6000+DS100/11.2012